



30尺双翼中英文配置单

Configuration Sheet for 30ft Expandable Unit (Chinese & English)

30双翼 30 wings	拓展尺寸 (L*W*H) Expand size (L * W * H)	9000mm*6540mm*2530mm	占地面积 cover an area	58.9m ²
	折叠尺寸 (L*W*h) Folding size (L * W * h)	9000mm*2220mm*2530mm	40柜装箱 40 container packing	1套 1 sets
指标 index	隔热性能 Thermal insulation performance	$\lambda=0.048W/m\cdot K$ 防火性能 Entering=0.048W/m · K fire resistance performance	抗风性能 wind-resistant performance	0.60kN/m ²
	隔音性能 Sound insulation performance	隔声量≥30dB Sound insulation level ≥ 30dB	防火性能 Fire performance	A级
	防水性能 Waterproof performance	降水量16mm/min无渗漏。 The precipitation is 16mm/min without any leakage.	抗震性能 Seismic performance	8级
	地面活载 Ground live load	2.0kN/m ²	屋面活载 roof live load	0.9kN/W ²
主框架 (全镀锌) Main frame (fully galvanized)	顶侧梁 Top side beam	60*120*4.25mm方管 60 * 120 * 4.25mm square tube		
	顶端梁 Top beam	折弯件2.5mm Bending part 2.5mm		
	底侧梁 bottom side rail	80*80*4.25mm方管 80 * 80 * 4.25mm square tube		
	底端梁 Bottom beam	折弯件2.5mm Bending part 2.5mm		
	铸铁吊头 Cast iron hanger head	铸铁吊头178*160*120 Cast iron hanger head 178 * 160 * 120		
	钢立柱 Steel column	折弯件2.5mm Bending part 2.5mm		
侧翼框架 (全镀锌) Side wing frame (fullv)	顶框架 Top frame	50*100*1.5mm方管 50 * 100 * 1.5mm square tube		
		折弯件2.0mm Bending part 2.0mm		
		35*80*60mm p型管 35 * 80 * 60mm P-type pipe		
		折弯件2.0mm Bending part 2.0mm		

底架 (镀锌) galvanized)	底框架 Bottom frame	40*80*1.5mm方管 40 * 80 * 1.5mm square tube
		80*80*1.5mm方管 80 * 80 * 1.5mm square tube
	折叠合页 Folding hinges	130mm镀锌合页 130mm galvanized hinges
侧墙 (全镀锌) sidewall (fully galvanized)	侧墙框架 Folding hinges	35*80*60mm p型管 35 * 80 * 60mm P-type pipe
		折弯件2.0mm Bending part 2.0mm
整体框架保护 涂料 Overall framework protection coating	喷涂 spray	静电喷涂塑粉烤漆≥80 Hm Electrostatic spraying plastic powder baking paint ≥ 80 Hm
墙板 wallboard	前后, 侧墙 Front and back, side walls	t70mm EPS彩钢板 T70mm EPS color steel plate
箱体 Box body	外部顶板 External roof panel	t50mm EPS彩钢板 T50mm EPS color steel plate
	内吊顶板 Interior ceiling panel	竹木纤维吊顶板 Bamboo and wood fiber ceiling board
	防水 waterproof	各活动关节D型胶条; 丁基防水胶带 D-type adhesive strips for each active joint; Butyl waterproof tape
地面 ground	结构板 Structural board	主地板为玻镁板, 厚度15mm; 两侧地板为15mm玻镁板 The main floor is made of glass magnesium board with a thickness of 15mm; The floor on both sides is made of 15mm glass magnesium board
门窗 doors and windows	入户门 Entrance doors	钢制单开门 (可选配其他门型) Steel single door (optional with other door types)
	外窗 External window	双层玻璃断桥铝窗尺寸: W930mm×h930mm, 8 (数量可定制 可选其他材料窗户) Double glass broken bridge aluminum window size: W930mm×h930mm, 8 (quantity can be customized and other materials can be selected)
	灯 lamp	LED圆吸顶灯15W/套。 LED round ceiling light 15W/set.
	插座 socket	标配国标三孔/五孔插座 (可根据客户要求配置插座标准) Standard configuration of national standard three hole/five hole sockets (socket standards can be configured according to customer requirements)

电气 electrical	开关 switch	双开, 单开 (可根据客户要求配置开关标准) Double open, single open (switch standard can be configured according to
	配电箱 Power Distribution Box	配电箱×1个, 带漏电保护器x1, 空开x3 Distribution box x1, with leakage protector x1, circuit breaker x3
	CEE工业插头 CEE Industrial Plug	220V, 50Hz, 3P64A×1个。 220V, 50Hz, 3P64A×1
	配线 wiring	入户线: 3*6平方, 空调插座: 3*2.5平方, 普通插座: 3*2.5平方, 照明: 2*1.5平方。(可根据不同国家定制符合认证要求电路) Entrance line: 3 * 6 square meters, air conditioning socket: 3 * 2.5 square meters, ordinary socket: 3 * 2.5 square meters, lighting: 2 * 1.5 square meters. (Circuits that meet certification requirements can be customized according to different countries)

NAME: LISA
 WHATSAPP: +86 13256382565
 WECHAT: +86 13256382565
 EMAIL: LISA@HONGRUNHOUSE.COM
 WEBSITE: WWW.HONGRUNHOUSE.COM

